

## Rough Terrain Forklift

Used Rough Terrain Forklift Nebraska - Forklift trucks utilize two forks to transport pallets and load and unload cargo. Forklifts fall into two main categories, industrial forklifts and rough terrain forklifts. Ideal for working on surfaces that are level and smooth, industrial forklifts are mostly utilized for warehouse applications and loading dock situations. Ideal for uneven terrain and rocky locations, rough terrain forklifts travel well in difficult environments. Due to size, tires, and weight capacity, a rough terrain lift is primarily used outdoors, often at construction sites. The main difference between industrial and rough terrain forklifts is that industrial forklifts are fitted with cushion tires, a common, over-the-road type tire. Pneumatic tires are utilized by rough terrain models. They are similar to tractor tires that offer more traction and flotation. Industrial forklifts can be powered by internal combustion engines but are more frequently powered by an electrical source, such as battery or fuel cell whereas rough terrain forklifts are almost always powered by an internal combustion engine.

**Types of Class 7 Rough Terrain Forklift Trucks**

There are three main types of Class 7 Rough Terrain Forklift Trucks:

1. Straight mast forklifts;
2. Telehandler forklifts; and
3. Rotating telehandler forklifts.

Regardless of its type, all rough terrain forklift trucks are designed to handle, as their name suggests, natural rough terrain and disturbed rough terrain typical of construction and military sites. The rough terrain models travel and perform well in difficult locations. In the case of rough terrain forklift operations, extra consideration must be given while raising loads in these rough, variable conditions to prevent tip-over. For safety reasons, it is vital the forklift maintains stability before moving, lifting or lowering. Adequate stability and proper lifting techniques need to be implemented to keep the forklift stable on the ground.

**Straight Mast Forklifts**

Straight mast forklifts are designed to transport building materials around a range of rough terrain sites such as demolition and construction sites. Pneumatic cushion tires allow this forklift better maneuverability and accessibility around difficult terrain. These allow the forklift truck to easily travel over rough terrain on the worksite. The majority of straight mast forklifts come in both two wheel and four wheel drive capabilities. Most straight mast forklifts are powered by diesel or propane fuel, allowing them to be used indoors for short periods but are more suited to outdoor applications. Both standard and straight mast forklifts offer similar lifting capacities weighing from 5000 to 36,000 pounds, depending on the model.

**Telehandler or Telescopic Handler Forklifts**

The distinct telescoping boom on telehandlers and telescopic handler forklifts contribute to the unit's name. Telescoping booms are handy for allowing the machine to load and place items at different lift heights and distances in front of the forklift. The reachability of the forklift provides the operator with greater flexibility when placing a load. Standard telehandler forklift units are long and low. They are designed with two wheels located at the front of the forklift with a different pair of wheels found close to the end of the unit. The telescopic boom can be found at the back of the forklift, mounted on a pivot that is attached many feet higher than the frame of the unit. The hydraulic fluid tank and fuel tank are mounted on the opposite side of the cab which is usually situated on the left side of the forklift. Along the center of the machine, the engine and transmission can be found inside the frame. This common configuration allows for a balanced forklift which is necessary for the basic stability of the machine which lifting, transporting and lowering loads.

Telehandler forklifts provide much greater lift heights when compared to a standard forklift. High-reach telehandlers can extend their full load capacity to 56 feet. The compact telehandlers can extend their full load capacity from 18 feet. Load capacities are between 5K to 12K pounds. All-terrain forklifts often include all-wheel steering which allows for greater maneuverability. This, along with power shift transmission and other steering features, means that the operator can move the lift in as close proximity to the work area as possible. The latest telehandler models feature ergonomic upgrades for ultimate operator comfort. Operator comfort is enhanced via larger cabs and tilted steering. These ergonomic upgrades have been shown to lessen repetitive stress injuries and lessen operator fatigue. Most telehandler forklifts rely on a single joystick. The joystick is responsible for the hydraulic system and the boom

operations. These machines can use non-marking tires to allow them to be suitable for maintenance in stadiums and on buildings or billboards and sign operations. Rotating Telehandler or Roto Telescopic Handler Forklifts Roto telescopic handler forklifts or rotating telehandlers have numerous items in common with the standard telehandler model. Telehandlers are capable of rotating heavy-lift weights to tremendous heights. This unit's added turntable and rotation flexibility increases the types of jobs it can complete. Rotating the forklift a complete three-hundred-and-sixty degrees creates a larger working location without the need of repositioning the forklift. With rotating telehandlers, one joystick handles the lift capacity and a second joystick is responsible for the rotation factor. Power-assist steering minimized slip differential on the rear axle for additional traction and four-wheel drive are some of the extra features offered on rotating telehandlers and standard telehandler models. Of course, a machine that can rotate has extra safety considerations to understand. Rotating telehandler rough terrain models come with standard stabilizers to establish more safety while rotating loads back and forth. There are some rotating telehandlers that are designed to move heavy weights without stabilizers to reduce the time it takes to reposition the forklift for work in other areas of the jobsite. Rotator telehandlers are usually smaller than their fixed cab counterparts, the standard telehandler. Therefore, rotator telehandler units can access smaller loads when compared to standard telehandler units. Rotating telehandlers offer load capacities ranging from 4000 to 10,000 lbs. and lift heights between fifteen to eighty feet. Standard and rotator telehandlers can double as a crane when outfitted with specific winch accessories. This means that these forklifts can sometimes allow a project to forego the need for a crane at the jobsite, saving time, expense and workspace. Advancements for Rough Terrain Forklifts Popular rough terrain forklift attachments include rotating fork carriages, booms, articulating booms and winches. Forklift attachments are vital for diversifying the machine. They will continue to be developed for years to come. However, the bulk of advancements are expected to be in the form of safety features, built-in to manufactured rough terrain forklifts. The latest safety upgrades include automatic load restriction and other features. By automatically weighing a load, these systems calculate the loads' safe reach distance while taking the boom angle and its' extension into account. If the safe reach distance is reached, an alarm will sound, warning the operator to make the proper adjustments to either the boom angle, the reach distance or load weight.